

Spin detection using a nanotube mechanical resonator

C. Urgell,

S. L. De Bonis¹, S. Hurand¹, J. Moser², J. Güttinger³, Q. Dong⁴, Y. Jin⁴, I. Khivrich⁵, A. Benyamini⁵, S. Ilani⁵, A. Eichler⁶, C. Degen⁶, and A. Bachtold¹

¹ICFO-Institut de Ciències Fotoniques, Mediterranean Technology Park, 08860 Castelldefels (Barcelona), Spain

²Institute of Modern Optical Technologies 1, Soochow University, Suzhou 215006, P. R. China

³II. Physikalisches Institut, RWTH Aachen 52056 Aachen, Germany

⁴Laboratoire de Photonique et de Nanostructures, CNRS, Marcoussis 97460, France

⁵Department of Condensed Matter Physics, Weizmann Institute of Science, Rehovot 76100, Israel

⁶Department of Physics, ETH Zurich, Otto-Stern-Weg 1, 8093 Zurich, Switzerland

sergio-lucio.debonis@icfo.eu

Micro-scale mechanical resonators are highly sensitive force sensors, enabling the detection of very small ensembles of nuclear spins [1]. Recently, we showed that mechanical resonators made of suspended carbon nanotubes display outstanding properties, such as quality factors up to 5 million, and force noise as low as 10^{-21} N Hz^{1/2} [2]. We propose to use this excellent sensitivity capability to detect and manipulate the nuclear spins of the ¹³C atoms naturally present in the carbon nanotube. For this, we use the specific nuclear magnetic resonance protocol developed by Nichol et al. [3] and a

metallic nanowire patterned very close to the nanotube to generate both the oscillating magnetic field and the magnetic field gradient, which are needed to manipulate the nuclear spins of the nanotube, and to detect them.

References

- [1] H. J. Mamin, M. Poggio, C. L. Degen, D. Rugar, *Nature Nanotech.* **2**, 301 (2007); C. L. Degen, M. Poggio, H. J. Mamin, C. T. Rettner, D. Rugar, *PNAS* **106**, 1313 (2009).
- [2] J. Moser, A. Eichler, J. Güttinger, M. I. Dykman, and A. Bachtold, *Nature Nanotech.* **9**, 1007 (2014).
- [3] M. Nichol, E. R. Hemesah, L. J. Lauhon, R. Budakian, *Phys. Rev. B* **85**, 054414 (2012).

