

An autonomous perovskite solar farm enabled by 2D materials

Emmanuel Kymakis

Department of Electrical & Computer Engineering, Hellenic Mediterranean University, Heraklion, Crete, Greece.

kymakis@hmu.gr

During the past decade, there was intensive research on the development of perovskite solar cells (PSCs), which have emerged as an alternative efficient energy harvester for both IoT devices and solar farms. The power conversion efficiency (PCE) of PSCs has rapidly increased and is now approaching the state-of-the-art PCE of 26.1%¹ obtained by crystalline-silicon PVs. However, this impressive PCE obtained on small-area cells and in laboratory conditions should be also valid to large-area PV panels in real outdoor conditions. Interface engineering, using solution processable 2D materials (e.g., graphene and transition metal dichalcogenides) is an effective approach to increase the readiness of this technology for manufacturing. The incorporation of the 2D materials improves the charge dynamics of the interfaces and most importantly protects the perovskite layer against diffusion of external agents, such as oxygen and moisture and the metal ion migration². In this context, the Graphene Flagship partners University Rome Tor Vergata, BeDimensional S.p.A, Greatcell and Hellenic Mediterranean University demonstrated the validity of this technology through the entire value chain, from materials development, perovskite modules and panels fabrication and their integration in an autonomous solar farm, to outdoor field tests, and assessment of the real energy production output. The main validation of the proposed approach is the realization of an autonomous solar farm, consisting of 5m² perovskite PV panels in the HMU campus at Crete³. A continuous monitoring of the solar farm was performed through in-house developed maximum power point trackers, coupled with a correlation of the environmental conditions, recorded by a weather station, with the outdoor performance of farm. The assembled solar farm delivered peak power exceeding 260W, proving the scalability of the proposed technology. The energy production of the solar farm was monitored for 12 months, demonstrating a remarkable 20% reduction (T_{80}) of the PV performance over 8 months of operation. Moreover, the solar farm's electrical characteristics were monitored as a function of temperature and light intensity. The data analysis demonstrated that the perovskite panels enabled by 2D materials are promising for outdoor operation at elevated temperatures, such as in high-irradiance global locations.

References

- [1] <https://www.nrel.gov/pv/assets/images/efficiency-chart.png>
- [2] Bellani, et al. Chem. Soc. Rev. 50, 11870– 11965 (2021)
- [3] S. Pescetelli, et al. Nature Energy (2022).



Figure 1: A photograph of the solar farm