

Dynamic Spray-Gun Deposition: a new way of conceiving the lego view for 2D and 1D nanomaterials

Paolo Bondavalli, Gregory Pognon, Lilia Quassym, Louiza Hamidouche, Clemence Rogier, Christophe Galindo,

Thales Research and Technology, 1Av. Fresnel, 91767 Palaseau, France
 Paolo.bondavalli@thalesgroup.com

Abstract

This contribution deals with the fabrication of devices based on graphene based nanomaterials using dynamic spray-gun deposition method implemented through roll-to-roll. We used this technique to fabricate sensors, supercapacitors [1], flexible memories [1] and conformable Electro-Magnetic interference Shielding (EMI) layers. In the first case we exploited the nanostructuration of mixtures of graphene and carbon nanotubes (CNTs) to achieve electrodes for supercapacitors. Indeed the MWCNTs are used as sort of spacers to avoid the restacking of graphene. Thanks to that we can exploit the huge surface of graphene to store charges and at the same time we create channels between the layers allowing the rapid charge and discharge of the device. The use of high quality graphene (<5 layers) and MWCNTs, with a diameter of around 20nm, also improve the conductivity for the electrodes and allowed us obtaining an impressive specific power value of around 100kW/Kg using an industrially suitable technique and not only a lab based one [2-3]. The spray-gun deposition method has been also implemented in the fabrication of GO and CNFs Oxidized based memories. In this case we case spray nanomaterials water based suspensions on a flexible layer previously metallized. The total thickness is around 100nm. After contacting the top with metallic contacts we are able to achieve flexible non volatile memories simply applying a bias (<3V). These memories show bipolar behavior and have been cycled 10000 times. They constitute one of the first examples of information storage devices that can be fabricated using a roll-to-roll implementable method. Finally, we have achieved EMS architectures using nanostructuration of graphene, MWCNTs and carbon nanofibers between polymers layers in order to exploit the Maxwell-Wagner-Sillars effect to absorb X-band frequencies. Thanks to this nanostructuration we are able to trap the charges in sort of micro-capacitors created in the layers. This is a real breakthrough considering that usually heavy metal based layers are used and that in this case mm based conformable layers can be obtained opening the route for new kinds of applications. Also in this case the fabrication will be implemented by roll-to-roll fabrication. During the presentation we will show all the details on the first characterization of devices and we will show also perspectives for other potential field of applications.

References

1. Graphene and Related Nanomaterials 1st Edition, Properties and Applications, Paolo Bondavalli, Hardcover ISBN: 9780323481014, Elsevier, Published Date: 1st September 2017, 192p.
2. MRS Advances, P.Bondavalli, G.Pognon, E.Koumoulos, C.Charitidis, <https://doi.org/10.1557/adv.2018.65>, 15 January 2018
3. F. ChemNanoMat, Ansaldo, A., Bondavalli, P., Bellani, S., Del Rio Castillo, A. E., Prato, M., Pellegrini, V., Pognon, G. and Bonaccorso,., 3 (6) 2017, pp 436–446
4. Supercapacitor electrode based on mixtures of graphite and carbon nanotubes deposited using a new dynamic air-brush deposition technique, P Bondavalli, C.Delfaure, P.Legagneux, D.Pribat J ECS 160 (4) A1-A6, 2013
5. Non-faradic carbon nanotubes based supercapacitors : state of the art, P.Bondavalli, D.Pribat, C.Delfaure, P.Legagneux, L.Baratton, L.Gorintin, J-P. Schnell, Eur. Phys. J. Appl. Phys. 60,10401, 2012